

Technical Datasheet

ERM1200GM Natural Gas CHP Unit



Energy Balance and Part Load Data @ 0.95PF		Units	100%	75%	50%
Electrical Output	(+/-3%)	kW	1250	938	625
Electrical Efficiency (LHV)	(+/-5%)	%	43.6%	42.2%	40.1%
Heat Output	(+/-10%)	BTU/min	55921	46393	35534
Thermal Efficiency (LHV)	(+/-8%)	%	35.4%	37.9%	41.3%
Fuel Input (LHV)	(+/-5%)	BTU/min	158114	122541	86048
Total Efficiency (LHV)	(+/-8%)	%	79.0%	80.1%	81.4%
Heat Output from Jacket Water	(+/-8%)	BTU/min	19513	17054	14302
Heat Output from Exhaust Gas (Cooled to 248°F)	(+/-8%)	BTU/min	36408	29339	21233
Intercooler Heat Output	(+/-8%)	BTU/min	14780	8336	3532
Radiated Heat Output	(+/-8%)	BTU/min	6906	6209	5837
Combustion Air Flow	(+/-5%)	SCFM	3207	2713	1925
Fuel Volume Flow (LHV = 924 BTU/SCFM)	(+/-5%)	SCFM	171	133	93
Exhaust Mass Flow	(+/-5%)	lb/h	15192	12798	9076
Exhaust Volume Flow (Cooled to 248°F)	(+/-5%)	ACFM	4516	3804	2698
Steam Option: Steam boiler output @ 15 psig	(+/-5%)	lb/h	2310	TBC	TBC
Chiller Option: Absorption chiller output	(+/-5%)	Tons	160-215	TBC	TBC

Engine Details

Manufacturer	Mitsubishi
Model	GS16R2-PTK
Fuel Type	Natural Gas
Min. Methane Number	60
Cylinders	16
Aspiration	Turbocharged/IC
Speed at Engine	1200 rpm

Secondary Water Details

Max. Water In/Out Temp.	°F	160/183
Max. Water Flow Rate*	GPM	330
Max. Glycol Content	%	50
Connection Size	in (mm)	4 (101.6)
Connection Type		ANSI B16.5 Class 150
Pressure Loss	PSIG	TBC
Max. Test Pressure	PSIG	150

Exhaust Details

Connection Size	in (mm)	12 (304.8)
Outlet Temp	°F	248
Max. Allowable Backpressure at Engine...	inH2O	20.0

Ventilation Details

Connection Size	in (mm)	TBC (TBC)
Ventilation Rate	ACFM	TBC
Max. Air Inlet Temp.	°F	85
Max. Air Outlet Temp.	°F	115

Intercooler Details of Engine

Max. Coolant Inlet Temp at Engine.	°F	95
Coolant Flow Rate	GPM	132
Connection Size	in (mm)	1 (25.4)
Max. Glycol Content	%	50

Generator Details

Manufacturer	Stamford	
Model	PI736F-312	
Type	Synchronous	
Voltage	V	480
Phase	Ph	3
Frequency/Speed	Hz/RPM	60/1200
Ingress Protection		IP23
Insulation Class		H
Rated Power Factor	PF	0.8
Rated Apparent Power at 80°C Rise	kVA	1563
X'd Dir. Axis Sub-Transient		0.13
T" Sub-Transient Time Const.		0.016

Electrical Details

CHP Breaker Size	A/Ph	2500
Current Per Phase @ 0.8PF	A	1879
Current Per Phase @ 0.95PF	A	1583
Efficiency @ 0.8PF	%	96.5%
Efficiency @ 0.95PF	%	97.1%

EPA Certified Engine Emissions at 100% Load

NOx	g/BHP-h	1.00
CO	g/BHP-h	0.30
NMHC	g/BHP-h	0.50

Low NOx Engine Emissions

NOx	g/BHP-h	0.60
CO	g/BHP-h	0.30
NMHC	g/BHP-h	0.50

Noise

Enclosure SPL	@ 23 ft	Standard/Low	75/TBC
---------------	---------	--------------	--------

Fuel Details

Main Supply Connection Size	in (mm)	3/76.2
Main Supply Connection Type		ANSI B16.5 Class 150
Min. Main Supply Pressure	PSIG	2.5
Min. Pre-Chamber Supply Pressure	PSIG	50
Main/Pre-Chamber % Total Volume	%	90/10

NB: Energy balance data is stated at ISO 3046-1 conditions. Values for part load are estimates only. Noise data stated at free-field conditions. All information detailed is for guidance only and is subject to change without notice due to our commitment to continuous improvement - all values should be confirmed with ER on a project specific basis.